



AssetPack™



Solar-powered, ruggedized global two-way asset tracking and sensor gateway for unpowered and powered assets.

The AssetPack™ (AP) is a durable, multi-functional device designed to provide low cost of ownership with long 10 year service life and easy installation and maintenance features.

The device is a self-contained, low profile, environmentally sealed asset gateway, powered by an energy efficient solar-rechargeable battery engineered to survive long low sun conditions and provide up to 10 years of data with zero maintenance. The AP can be mounted on almost any type of asset used in the world's harshest conditions. Because it is intrinsically safe, it can be used in hazardous locations (HAZLOC) to track hazardous material shipments (HAZMAT) or monitor hazardous operations.

The AP features advanced memory-rich, on-board processing capabilities supporting highly configurable modes of operations, business logic, reporting rates, alert thresholds, on-board geofences and configurable IO interfaces for various sensor-based applications. Everything is configurable over the air.

The AP leverages the 100% reliable global two-way coverage of the Iridium satellite network and/or next generation cellular technology providing seamless uninterrupted connectivity and access to fixed and mobile assets anywhere.

The AP delivers actionable information that helps businesses optimize operational efficiencies and reduce cost making this device an ideal solution for tracking and managing of almost any unpowered asset such as trailers, containers, vessels.

The AP can be remotely managed through the AssetLink DeviceManager user interface or via API so that actionable information can be visualized through any AssetLink Value Added Reseller or customer data system.



Experience The Robust Flexibility

10 year service life with zero maintenance

Solar-rechargeable battery with power save modes

Easy installation - installs in minutes

IP67 Rugged enclosure

Intrinsically Safe for HAZLOC and HAZMAT

True two-way, 100% global connectivity

On-board geofencing for immediate arrival and departure alerts

On-board memory for advanced sensor-based applications

Over-the-air and local programming

Configurable IOs –interface cable

Published API for VAR Integrations – device and data integrations

Built-in motion sensor

Built-in temperature sensor

Optional AES 256 Encryption

AssetPack™ Specifications

Form Factor

Enclosure 12.4" x 3.2" x 1.15"
(31.50 x 8.1 x 2.9 cm)

Weight 18.9 oz (535 g)

GPS

Location Accuracy <5m (50%) CEP

Acquisition & Tracking Sensitivity -161.5 dBm

Cold start (open sky) 33s

Hot start (open sky) <2s (typical)

Interfaces

Harness Connector 8 pin circular

Inputs/Outputs Analog or Digital In/Out (2)

Serial RS 485 (1), MODBUS, CANBUS/J1939

On/Off Multi-function switch

Sensor Power Capability 7-8VDC or higher depending on sensor

Communications

Satellite Only Iridium Short Burst Data
1616-1626.5 MHz
Time Domain Duplex TDMA/FDMA

Cellular Only 4G LTE Cat-4/3G (North America)
3G HPSA/2G (Global baseline)

Hybrid Cellular/Satellite lowest cost routing

Power

Battery Solar Rechargeable Battery:
5300 mAh, 7.2VDC

Cycles 100% DOD >1000 cycles

Shelf life (Charged) >3 years (inventory mode)

Solar Panel Mono-crystalline silicon 6V, 1W

External Power 10-18V, up to 500 mA

Environmental

Temperature (operating) -40° C (-40° F) to +70° C (+158° F)

Humidity 100% at 50° C, salt, fog per MIL STD 810

Shock/Vibration MIL STD 810 and SAE J1455

Water/Dust IP67/NEMA6, waterproof full immersion at 1m depth

Certifications

FCC CFR parts 15 and 25
Industry Canada CAN ICES-3 (A) / NMB-3 (A)
CE Mark
ETSI EN 301 489-1 V1.9.2 & EN 300 440-2
UL/CSA/EN/IEC 61010-1
ANSI/ISA 12.12.01-2000 Class I, Division 2
CAN/CSA C22.2 No. 213 Class I, Division 2
ATEX Zone 2 Compliant (with ATEX cage)

Mounting Options

Magnet mount
VHB Tape
Flat Plate mount with Self-tapping Screws
Rugged cage
ATEX protective cage

Accessories

Engine run time harness
Tamper alert trigger switch
Temperature sensor
Panic button
Magnetic door sensor
Container security cable
Multi-functional interface cable
Magnetic and door mount brackets
Protective cage
ATEX cage

LEARN MORE ABOUT THE
ASSETPACK'S INDUSTRY
APPLICATIONS



WWW.ASSETLINKGLOBAL.COM/RESOURCES

AssetLink Global

AssetLink is a leader in satellite-enabled hardware and IoT systems implementation, design, and manufacturing. AssetLink builds best in class GPS satellite, cellular tracking and sensor-interface hardware, and delivers comprehensive hardware, data services and information access to industrial, Fortune 500 and government clients worldwide. AssetLink connects enterprises with their equipment and assets, no matter how remote. AssetLink is focused on partnering with VARs, Resellers, and Integrators to distribute the "Forever, Everywhere" AssetPack (AP) global tracker.

2018.05.28

M2Mconnectivity

sales@m2mconnectivity.com.au

www.m2mconnectivity.com.au

+61 3 9696 3011