



## Single Channel LoRaWAN® Operated Low Power Transmission Interface for Industrial Applications

- Compatible with all LoRaWAN® frequencies
- Wide range of industrial applications
- Designed to meet outdoor applications
- Long-term durable performance in harsh environment
- Ultra-low power



## TECHNICAL SPECIFICATION

### Sensor Interface

<ul style="list-style-type: none"> <li>• <b>Interface options:</b> (RS1-N covers a wide range of industrial sensors interfaces. Unique design of the interface gives ultimate flexibility of choosing the right sensor interfaces)</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Analogue:</b> mV / mV/V / 4-20mA/ 0-5V / 0-10V</li> <li>• <b>Digital:</b> I2C / RS232/ RS485/ Modbus/ HART/ SDI12/ TTL UART</li> <li>• <b>Temperature:</b> Pt100, 2 or 3 wire; Pt1000, 2 or 3 wire</li> <li>• <b>Pulse:</b> Pulse (Reed Switch) (or other customised options on request)</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Electric Connection:</b></li> </ul>	1m cable, pin connection (or other options on request)
<ul style="list-style-type: none"> <li>• <b>Operating temperature range:</b></li> </ul>	-10 ~ + 70 °C

### Power

<ul style="list-style-type: none"> <li>• <b>Power Supply:</b></li> </ul>	Built-in Replaceable Lithium Battery, External Power (option)
<ul style="list-style-type: none"> <li>• <b>Rated Voltage</b></li> </ul>	3.6 V
<ul style="list-style-type: none"> <li>• <b>Battery Lifetime:</b></li> </ul>	Typ. 50,000+ readings and 10,000+ transmission (More than 10 years for most applications)

### Physical Specification

<ul style="list-style-type: none"> <li>• <b>Materials:</b></li> </ul>	ASA or POM
<ul style="list-style-type: none"> <li>• <b>Weight:</b></li> </ul>	350 g
<ul style="list-style-type: none"> <li>• <b>Protection Rate:</b></li> </ul>	IP65 /IP67, UV Protected -

### Communication

<ul style="list-style-type: none"> <li>• <b>LoRaWAN® Version, Class:</b></li> </ul>	1.0.2revB, Class A (Class C on request)
<ul style="list-style-type: none"> <li>• <b>LoRaWAN® Frequency Zone:</b></li> </ul>	AS923, EU868, US902-928, AU915-928 (other zones available on request)
<ul style="list-style-type: none"> <li>• <b>LoRaWAN® Activation Type:</b></li> </ul>	OTA (default), ABP
<ul style="list-style-type: none"> <li>• <b>Sampling Type:</b></li> </ul>	Periodic (default), Event triggered
<ul style="list-style-type: none"> <li>• <b>Sampling Period:</b></li> </ul>	Configurable via downlink (default 4 hours)
<ul style="list-style-type: none"> <li>• <b>Transmission Type</b></li> </ul>	Per sample (default), Event triggered, Conditional
<ul style="list-style-type: none"> <li>• <b>Parameter Configuration:</b></li> </ul>	Over-the-air via LoRaWAN® downlinks Locally via wireless connectivity
<ul style="list-style-type: none"> <li>• <b>Firmware update:</b></li> </ul>	Locally via wireless connectivity, Over The Air

## NETWORK CONNECTION AND VISUALISATION

### Network Integration

Integratable to all main networks (Actility, Alibaba, Cisco, Digita, Everynet, GeoWAN, Kerlink, kpn, Lorient, machine-Q, Objenious, Orange, Orbiwise, Proximus, Senet, Sens, Swisscom, TATA, The Things Network (TTN), TTI and any other network)

### Visualisation and Data Management

Ellenex white label microservice platform and Integratable to all main IIoT platforms directly or through the API(AWS, Azure, PTC ThingWorx, Bosch IoT, Cisco Jasper & Kinetic, Sierra Numerex, MathWorks ThingSpeak, GE Digital Predix, LandisGyr, Siemens MindSphere, Cumulocity, myDevices, Ubidots, TagoIO, AllThingsTalk Maker, HPE IoT and any other major IoT platform).

### Ellenex Platform Main Features

- Encrypted ultra-low power communication protocol
- Advanced device inventory
- Integration APIs for enterprise systems
- Multi-tenant role-based access control
- Data export and import
- White-label platform for enterprise runs on private account
- Variable alarm setting for high and low thresholds and multi-channel alerting
- Sampling and transmission interval configuration
- Transmission condition configuration
- Other configurations and customisation available on request



Encrypted & ultra-low power



Integratable



Dynamic alerting



Multi-tenant



Scalable





Composable & API first

# RS1-L Spec-sheet



## MODEL GUIDE

C Model:		E Model:	
	<p><b>C model</b> comes with cylindrical shape housing suitable for battery operated applications with IP68 rate and clamp mounting. This model has 2 option of 4 wire cable connection and the 4pin connection.</p>		<p><b>E model</b> comes with rectangular shape housing suitable for battery or external power operated applications with IP65 rate, and wall mounting. This model has 2 option of 4 wire cable connection and the 4pin connection.</p>

## INDUSTRIES



Water & Environment



Agriculture & Farming



Oil & Gas



Marine & Oceanography



Mining & Construction



Smart Building & HVAC



Transport & Logistics



Food & Beverage



Hydraulics and Compressed Air Systems

## APPLICATIONS

- Pump Performance Monitoring
- Water Pipeline Pressure Monitoring
- Pressurised System Monitoring
- Chiller and Cooling System Monitoring
- Hydraulic and Pneumatic Systems Monitoring
- Liquid Storage Level Monitoring
- Spraying System Monitoring
- Air Compressor Monitoring

## ORDERING CODE

RS1-L									
Frequency Zone									
AS (AS923)		EU (EU868)		USx (US902-928, sub-band x)		AUx (AU915-928, sub-band x)		Others	
LoRaWAN® Activation									
A (Over The Air Activation - OTAA)					P (Activation By Personalization ABP)				
Interface Options									
A1: I2C			B1: Pulse (Reed Switch)						
C1: 4-20mA		C2: 0-10V		C3: 0-5V		C4: mV or MV/V			
D1:Pt1000 (2 wire)		D2: Pt1000 (3 wire)		D3:Pt100 (2 wire)		D4: Pt100 (3 wire)			
E1:RS232		E2:RS485		E3: SDI12		E4: TTL UART			
E5: Modbus		Other customised options on request							
Electric Connection									
P (pin connector)					3m (3m wire cable)				
P68 (pin IP68 rated connector)					Others as specified				
Enclosure									
C: Compact <small>(Material: POM) Available only with cable connection</small>			E: Rectangular <small>(Material: ASA)</small>			X: without housing <small>(only board)</small>			
Others									
Device Activation									
S: on/off switch					N: NFC <small>(by mobile phone)</small>				
X: No switch <small>(always on)</small>					D: Dual switch <small>(on/off + Trigger)</small>				
Antenna									
I: Internal					E: External				
Options									
G: GPS tracker									
Other Options on request									
RS1-L	AS	A	C1	P	E	S	E		

### Sample Product Code:

- RS1-L-AS-A-P-E-S-E

Single channel LoRaWAN sensor interface operated on frequency AS923, over the air activated (OTAA), for 4-20mA output, with rectangular housing, activated by on-off switch and external antenna.